



AB-GTM24CT-230VI

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



KEY FEATURES:

- Inverter technology
- Multi-speed capability
- BlueFin coating protection
- Built-in Smart Sync technology



SPECIFICATIONS:

Indoor Model			AB-GTM24CT-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	24,000
Heating	Rated Capacity	Btu/h	24,000
Minimum Circuit Ampacity (MCA)		A	
Max. Fuse		A	5
Indoor Air Flow (Hi/Mi/Lo)		CFM	824
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	47/46/43
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	1"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/5/8"
Dehumidification		Pnt/H	5.43
Communication wiring			AWG 16-4
Indoor	Dimension (W×D×H)	Inch	33.07×33.07×9.69
	Packing (W×D×H)	Inch	35.83×35.83×12.20
	Net/Gross Weight	lbs.	52.9/61.7



AB-GTM24CT-230VI

