



AB-GTM09FC-230VI

Job Name: _____
 Location: _____
 Engineer: _____
 Submitted to: _____
 Submitted by: _____
 Reference: _____

Date: _____
 Approval: _____
 Construction: _____
 Unit #: _____
 Drawing #: _____



KEY FEATURES:

- Inverter technology
- Multi-speed capability
- BlueFin coating protection
- Built-in Smart Sync technology



SPECIFICATIONS:

Indoor Model			AB-GTM09FC-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	9,000
Heating	Rated Capacity	Btu/h	11,000
Minimum Circuit Ampacity (MCA)		A	
Max. Fuse		A	5
Indoor Air Flow (Hi/Mi/Lo)		CFM	500
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	36/34/31
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	1"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/3/8"
Dehumidification		Pnt/H	1.48
Communication wiring			AWG 16-4
Indoor	Dimension (W×D×H)	Inch	39.37×9.25×27.17
	Packing (W×D×H)	Inch	42.52×12.80×30.32
	Net/Gross Weight	lbs.	57.3/67.2



AB-GTM09FC-230VI

