



AB-GTM07WM-230VI

Job Name: _____

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Date: _____

Approval: _____

Construction: _____

Unit #: _____

Drawing #: _____



KEY FEATURES:

- Inverter technology
- Multi-speed capability
- BlueFin coating protection
- Built-in Smart Sync technology



SPECIFICATIONS:

Indoor Model			AB-GTM07WM-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	7,000
Heating	Rated Capacity	Btu/h	7,000
Minimum Circuit Ampacity (MCA)		A	
Max. Fuse		A	
Indoor Air Flow (Hi/Mi/Lo)		CFM	353
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	38/35/30
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	2/3"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/3/8"
Dehumidification		Pnt/H	1,48
Communication wiring			AWG 16-4
Indoor	Dimension (W×D×H)	Inch	31.02×11.50×7.80
	Packing (W×D×H)	Inch	34.65×14.57×11.42
	Net/Gross Weight	lbs.	17.60/22.00



AB-GTM07WM-230VI

