



AB-GTM18WM-230VI

Job Name: _____

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Date: _____

Approval: _____

Construction: _____

Unit #: _____

Drawing #: _____



KEY FEATURES:

- Inverter technology
- Multi-speed capability
- BlueFin coating protection
- Built-in Smart Sync technology



SPECIFICATIONS:

Indoor Model			AB-GTM18WM-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	17,000
Heating	Rated Capacity	Btu/h	17,700
Minimum Circuit Ampacity (MCA)		A	
Max. Fuse		A	5
Indoor Air Flow (Hi/Mi/Lo)		CFM	618
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	45/40/35
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/1/2"
Dehumidification		Pnt/H	3.38
Communication wiring			AWG 16-4
Indoor	Dimension (W×D×H)	Inch	38.82x12.40x8.86
	Packing (W×D×H)	Inch	42.13x15.16x12.28
	Net/Gross Weight	lbs.	26.45/32.26



AB-GTM18WM-230VI

